



DCM Cinema Advertising Production Requirements

2K Dolby Atmos Digital Cinema Exhibition

Please contact us directly with information about which advert you are working on and we will supply you with your login details to the DCM Content Hub.

.....

DCM will handle the creation of the DCP (Digital Cinema Package) from master materials and its digital distribution to DCM cinema screens for the campaign. Once we have received master materials and copy clearance/s we will invite you to a pre-distribution screening of the final DCP.

This document specifies the items that we require for the cinema production of **2K/HD commercials** with **Dolby Atmos** audio.

We advise allowing at least 48 hours for copy clearance submission and preparation of final assets.

Please note that a Digital Cinema 5.1 mix is also required for non-Atmos screens. Please complete the Dolby Atmos mix first - your sound studio can quickly & easily re-render the Atmos mix to 5.1.

Production requirements for 4K resolution visuals are also available on request. Please contact production@dcm.co.uk for further information.

Please note that copy supply from you to us is fully electronic.

.....

DOCUMENT CONTENTS

IMPORTANT CONTACT INFORMATION

STEP 1: COPY CLEARANCE

- [1.1](#) – Submitting to CAA
- [1.2](#) – Submitting to BBFC
- [1.3](#) – HFSS advertising regulations

STEP 2: TECHNICAL SPECIFICATIONS

- [2.1](#) – Notes
- [2.2](#) – Picture
- [2.3](#) – Audio (Dolby Atmos)
- [2.4](#) – Audio (Digital Cinema 5.1)

STEP 3: DELIVERY INSTRUCTIONS

- [3.1](#) – Picture Upload
- [3.2](#) – Audio Delivery (Dolby Atmos)
- [3.3](#) – Audio Delivery (Digital Cinema 5.1)



digital cinema media

IMPORTANT CONTACT INFORMATION

DCM

Grant Gulczynski
Production Manager

Grant.Gulczynski@dcm.co.uk

020 7534 6304

Sean Holden
Production Assistant

Sean.Holden@dcm.co.uk

020 7534 6217

Will Hallam
Production Business Director

Will.Hallam@dcm.co.uk

020 7534 6329

CAA

url: <http://cinemaadvertisingassociation.co.uk/>

email: submissions@cinemaadvertisingassociation.com

phone: **020 7199 2433**

BBFC

url: <http://www.bbfc.co.uk/>

email: helpline@bbfc.co.uk

phone: **020 7440 3299**

DOLBY TRANSFER SUITE

email: ContentServices@dolby.com

phone: **020 7406 3200 (Reception)**

phone: **020 7406 3188 (Direct)**

4CINE AUDIO CONFORMITY

url: <https://4cine.io>

email: administrator@4cine.io

phone: **07785 954220**

Digital Cinema Media
350 Euston Road
London NW1 3AX

T +44 (0)20 7534 6363
F +44 (0)20 7534 6464
W dcm.co.uk

Registered in England No. 06497707
Registered office: Regent's Place
350 Euston Road London NW1 3AX



STEP 1: COPY CLEARANCE

Cinema clearance in the form of final approval from the Cinema Advertising Association (CAA) is required in order to show an advertisement in cinema.

The CAA is the sole clearance body for most commercial advertising in UK cinemas.

However, the following types of advertising also require certification from the British Board of Film Classification (BBFC):

- Public information / campaigning films.
- All advertisements to promote films, DVDs, television channels, broadband suppliers and programmes (broadcast or download) that contain sequences of content, irrespective of length.
- All advertisements which contain content from films, DVDs, television channels, broadband suppliers and programmes (broadcast or download), irrespective of length.

1.1 – SUBMITTING TO CAA

The CAA Panel advise an approximate lead time of 48 hours to clear final copy following receipt of payment and video content. However, contentious copy will be referred to a Friday morning Copy Panel meeting.

Please submit final copy as soon as possible, with a view to confirmation by the copy deadline communicated to you by DCM.

You access the CAA submission form and all instructions here:

<https://cinemaadvertisingassociation.co.uk/how-to-submit/>

1.2 – SUBMITTING TO BBFC

If you are unsure whether your advertisement requires BBFC certification, please contact the BBFC Helpline (helpline@bbfc.co.uk / 020 7440 0299) who will be happy to advise you.

To apply for BBFC certification please fill out the “public information / campaigning film” submission form on the BBFC extranet: <http://www.bbfc.co.uk>

1.3 – HFSS

Please refer to the CAA for details on regulations for High Fat, Salt or Sugar (HFSS) for (Non-Broadcast) Cinema: <https://cinemaadvertisingassociation.co.uk/policies/>

.....



digital cinema media

STEP 2: TECHNICAL SPECIFICATIONS

2.1 – NOTES

- Please ensure that the Dolby Atmos audio is mixed against the same picture as the one you are supplying to DCM, to avoid sync issues in the process.
- Cinema runs at 24fps; however, you will note that we accept picture at either 24fps or 25fps.
- If you are supplying picture at 25fps, then your sound studio must mix against this same 25fps version. Your studio will need to stretch the audio to 24fps before supplying the finished Dolby Atmos & Digital Cinema 5.1 mixes to us, as per the audio specifications in this document. This means that the advertisement will run 4% slower/longer on cinema. (However, please note that DCM do not charge any additional fees for this 4% overrun).
- If it is preferable to avoid stretching the audio, then you may alternatively decide to talk to your post house about cutting a native 24fps picture before the mix which will avoid the tempo change.
- The Dolby Atmos & Digital Cinema 5.1 cinema mixes should be budgeted for by the creative agency, and mixed at a Dolby certified studio.
- Please contact DCM for our list of recommended sound studios which specialise in mixing for Dolby Atmos & Digital Cinema 5.1 cinema commercials.



STEP 2: TECHNICAL SPECIFICATIONS - PICTURE

PLEASE PASS THESE DETAILS TO YOUR POST PRODUCTION HOUSE

Production requirements for 4K resolution visuals are also available on request. Please contact production@dcm.co.uk for further information.

2.2 – PICTURE (2K/HD)

2K DATA TIFF Sequence		OR	HD DATA TIFF Sequence	
Ratio	1.85		Ratio	1.78
Whole Picture	1998x1080		Whole Picture	1920x1080
Cinema Title Safety	1798x972		Cinema Title Safety	1605x903

All legal lines must be positioned within Cinema Title Safety

- Bit depth** 8 - 16 bit accepted.
For best results please supply highest bit depth available, per source.
- Colour Primaries** rec709
- Range** Legal (Studio) 16-235 or Full (Extended) 0-255. Please indicate which has been used.
- Frame Rate** 25fps or 24fps
Frames should always be supplied progressive, NOT interlaced
- Length** TIFF sequence should contain active frames ONLY i.e. NO clock, end frame hold or black frames at start or end.

QuickTime is NOT accepted

Please do not supply alpha channels



STEP 2: TECHNICAL SPECIFICATIONS - AUDIO

(BOTH DOLBY ATMOS & DIGITAL CINEMA 5.1 ARE REQUIRED)

2.3 – AUDIO (DOLBY ATMOS)

Dolby Atmos is an immersive sound technology with overhead speakers and the ability to place up to 118 individual sounds (objects) anywhere within the 3D space of the cinema auditorium.

For the best results it is ideal for your sound studio to have access to **separate uncompressed stems** for the Atmos mix, including music stems. This is so that every sound can be individually placed within the 3D immersive sound environment.

(Although not recommended, stereo stems can be used but hugely limit your options in the Dolby Atmos mix environment).

Please contact your studio directly for their individual specifications and advice.

A Digital Cinema 5.1 mix is also required for non-Atmos screens. **Please complete the Dolby Atmos mix first** - your sound studio can quickly & easily re-render the Atmos mix to 5.1.

Dolby Atmos mix – RMU printmaster within a compressed .zip file

DCM only accepts Atmos audio from Dolby certified studios.

- There must be a 1 kHz synchronization pip 48 frames before the FFOA on the centre channel bed (1 frame in duration).
- Audio must run in synchronisation to the same picture being supplied to DCM when played back at 24fps (frames per second).
- FFOA needs to be set as either 01:00:00:00, 01:00:08:00, 10:00:00:00 & 10:00:08:00 (for clear & consistent recording time stamps).
- Please specify which on the Dolby Transfer Suite's Programme Information Form (PIF).
- RMU printmaster recording must start at least 10 seconds before the FFOA and recording
- must last for at least 5 seconds after the LFOA.

The maximum LEQ(m) level should be strictly 82dB.

- To ascertain the loudness LEQ(m) of an Atmos mix, measure the 7.1. re-render output with the following default settings:
 - Group Assignment: Full Mix
 - Surround Gain: 0dB
 - Bass Manage to LFE: Off
 - Bass Threshold Frequency: 0Hz
 - Overhead Contribution: 0dB
 - +3dB Surround Boost: ON



2.4 – AUDIO (DIGITAL CINEMA 5.1)

D-Cinema 5.1 mix – 6 x mono WAV files

DCM recommends the use of theatrical mix studios that meet typical motion-picture norms and standards such as ISO 2969 and ISO 22234, for the preparation of the final D-Cinema 5.1 master from high dynamic range original sound elements where possible.

All submissions MUST follow the DCM Submission Specification outlined here:

- The cinema sound mix and format must be 5.1 (Left, Right, Centre, LFE, Left Surround, Right Surround).
- No stereo mixes are permitted included those submitted within a wider 5.1 format.
- The submission must be as a set of separate single-track files of the same filename (except for the channel-id element) and strictly adopt the following filename convention:

Client-name_Content-Title-Version.Channel-ID.wav

and where the **Client-name** and **Content-Title-Version** fields must not include any underscore ‘_’ character, which is reserved, as per the following example:

Brand-XYZ_Autumn Collection (EN v2).L.wav
Brand-XYZ_Autumn Collection (EN v2).R.wav
Brand-XYZ_Autumn Collection (EN v2).C.wav
Brand-XYZ_Autumn Collection (EN v2).LFE.wav
Brand-XYZ_Autumn Collection (EN v2).Ls.wav
Brand-XYZ_Autumn Collection (EN v2).Rs.wav

- LFE channel must be filtered, with a recommended 125Hz 24dB/octave low-pass filter.
- The WAV files need to be at 48 kHz and 24-bit.
- Reference level is -20dBFS.
- No sync plop or leader.
- The maximum LEQ(m) level should be strictly 82dB as measured in accordance with ISO 21727 and BS 5550-7.4.2.

Additional responsibilities of the studio:

- WAV files should be the exact picture length and duration when played back at 24fps (frames per second).
- To ensure no problems with sync, line up the WAV with the picture where the first audio sample represents the very start of the audio associated with the very first picture frame.

Audio must run in synchronisation to the same picture being supplied to DCM when played back at 24fps (frames per second).



STEP 3: DELIVERY INSTRUCTIONS

3.1 – PICTURE UPLOAD

Connect to the [DCM Content Hub](#) and enter the login details supplied at the top of this document.

The Content Hub is best accessed using an FTP client (FileZilla or Cyberduck), but internet browsers can also be used ([Firefox](#) or [Chrome](#)).

Once connected, please follow the steps below to upload material:

- **Create a new folder and name it as per the naming convention/s below.**
- **Upload your TIFF image sequence to the folder.**
- **Unzipped image sequences are preferable. If compressing the sequence is unavoidable, please note that we only accept .zip (please do not use RAR).**
- **Please upload the image sequence in a folder named with the requested information as follows:**

Product_Title_Length_fps_ColourPrimaries_Range_clocknumber

We do not accept WeTransfer links or hard drives.

Please note that source material will be deleted from the server once the DCP is approved.

3.2 – AUDIO DELIVERY (DOLBY ATMOS)

Please instruct your sound studio to deliver your Atmos mix to DCM via the DCM Content Hub, following the below workflow

- Studio completes Atmos mix and encodes the final MXF delivery on-site.
- Studio upload Atmos MXF and encode report to DCM's Content Hub, and send a required confirmation email to DCM with Dolby cc'd for visibility - ContentServices@dolby.com.
- Dolby QC MXF file and encode report on-site and perform a file-based QC of the content
- Dolby reply back on the email thread with the studio and DCM to confirm the content has passed.



digital cinema media

3.3 – AUDIO DELIVERY (DIGITAL CINEMA 5.1)

Please instruct your sound studio be set up with a 4cine[®] account to deliver audio to DCM via 4cine.ibmaspera.com.

Do not upload Digital Cinema 5.1 mix to the DCM Content Hub.

- Upon receipt of audio, 4cine.io will run an essential technical QC evaluating the submission against the above DCM Submission Specification, which also ensures compliance with UK cinema audio volume regulations.
- 4cine.io alerts DCM once QC is complete and shares all QC-Passed submissions automatically with us for our subsequent DCP mastering with the Atmos mix and picture.

[®] 4cine is a registered trademark of Julian Pinn Ltd